

HSVB1606



IP68

IK08

24V

3
YR
WARRANTY



Key Features

- Minimum bend diameter - 50mm
- Ambient working temperature: MAX (+)95°C
- Bending Direction - Vertical
- Incremental Order Length (Monochrome) - 166.7mm
- Incremental Order Length (Tunable white) - 83.3mm
- Incremental Order Length (RGB / RGBW) - 100mm
- DMX/SPI Pixel Light options available on request

Connectors




Mounting Accessories

Aluminium
Profile



Accessory Dimensions



Code		Example: HSVB1617 - 068022DEDO-2400											
Code		Wattage (W/m)		CRI		CCT		lm/m	Connector		Driver		Length
HSVB1617	06	6W/m	80	CRI>80	22	2200K	350	DE	Direct Entry	DO	Non-Dim	-XXXX	
					27	2700K	400	SL	Left side entry	DA	DALI		
					30	3000K	450	SR	Right side entry	CA	Casambi		
					35	3500K	450	BE	Bottom Entry	SW	Switch Dim		
					40	4000K	450		PH	Phase Dim			
					57	5700K	450		RC	2.4Ghz Remote Control			
					65	6500K	450						
					TW	2200K - 5700K	450						
	04	3.6W/m											
	05	5W/m											

Lumen/m figures based on, 6W, CRI>80. ## HAWKO Lighting reserve the right to change any data without notification.
If this fitting needs to be adjusted on site, contact FOS Lighting before cutting the product
HAWKO Lighting - Neon Flex Range - 2023